

How to clean QMAIL mail server filled Queue with spam mail messages

Author : admin

Sys Admins managing QMAIL mail servers know, often it happens QMAIL queue gets filled with unwanted unsolicited SPAM e-mails due to a buggy *WEB PHP / Perl mail sendingform* or some other odd reason, like too many bouncing messages ,,,,

For one more time I've experienced the huge SPAM destined mails queue on one QMAIL running on Debian GNU / Linux.

= ... Hence I needed to clean up the qmail queue. For this there is a little tool written in PERL called **qmhandle**

A+) Download qmhandle;

[Qmhandle's official download site is in SourceForge](#)

I've made also a [mirror copy of QMHandle here](#).

```
qmail-server:~# cd /usr/local/src
qmail-server:/usr/local/src# wget -q http://www.pc-freak.net/files/qmhandle-1.3.2.tar.gz
```

B=) STOP QMAIL

As it is written in the program documentation one has to be very careful when cleaning the mail queue. Be sure to stop qmail with **qmailctl** or whatever script is used to shutdown any mail sever in progress operations, otherwise there is big chance the queue to mess up badly .

C#) Check extended info about the mail queue:

```
qmail-server:/usr/local/src/qmhandle-1.3.2# ./qmhandle -l -c
102 (10, 10/102) Return-path: anonymous@qmail-hostname.com
From: QMAIL-HOSTNAME
To: as1riscl1.spun@gmail.com
Subject: =?UTF8?B?QWNjb3VudCBpbmZvcmlhdGlvbiBmb3IgU09DQ0VSRkFNRQ==?=
Date: 1 Sep 2011 21:02:16 -0000
Size: 581 bytes
```

```
"""
1136 (9, 9/1136)
Return-path: werwer@qmail-hostname.com.tw
From: martin.georgiev@qmail-hostname.com
To: costador4312@ukr.net
Subject: Link Exchange Proposal / Qmail-Hostname.com
```

Date: Fri, 2 Sep 2011 07:58:52 +0100 (BST)

Size: 1764 bytes

1103 (22, 22/1103)

Return-path: anonymous@qmail-hostname.com

From: SOCCERFAME

To: alex.masdf.e.kler.1@gmail.com

Subject: =?UTF8?B?QWNjb3VudCBpbmZvcmlhdGlvbiBmb3IgaU09DQ0VSRkFNRQ==?=

Date: 2 Sep 2011 00:36:11 -0000

Size: 578 bytes

Total messages: 1500 Messages with local recipients: 0

Messages with remote recipients: 1500

Messages with bounces: 500

Messages in preprocess: 300

D-) Delete the Queue

```
qmail-server:/usr/local/src/qmhandle-1.3.2# ./qmHandle -D
```

.....

.....

Finally launch the qmail to continue normal oper.

```
qmail-server:~# qmailctl start
```
