

NCR**SPECIFICATION SHEET**
X-1014-7

Specification
395-0067096
Page 1 of 68

vision

F

1.0 SYSTEM

This specification defines the installation requirements for the NCR I82X0 system. Numerous configurations are available to the customer. The available units are listed below:

- A. C6080 Processor
- B. C6081 Processor
- C. C7621 Cassette Drawer
- D. C7622 Vertical-Mount Cassette
- E. C6560-0401, -0402 Disk Drive
- F. C6560-301 Disk Drive
- G. C7330 Magnetic Tape Deck (rack-mount or free-standing)
- H. C349 Line Printer
- I. C6420 Line Printer
- J. C260-7 Thermal Printer (KSR)
- K. C260-8 Thermal Printer (RO)
- L. C6440 Matrix Printer
- M. C368 Card Reader
- N. C796-101 CRT Terminal
- O. C7900-01, -11 CRT Terminal
- P. C6566 Fixed Disk Drive
- Q. C1566 Fixed Disk Power Supply (Single or dual)
- R. C7640 Flexible Disk Recorder (rack-mount or free-standing)
(single or dual drive)
- S. C6085 Auxillary Card Gage
- T. C6530 Disk Drive
- U. C6539 Peripheral Adapter


SPECIFICATION SHEET
 X-1014-7

Specification
395-0067096
Page 2 of 68

2.0 REFERENCES

Additional installation specifications will be required for the features and listed below:

2.1	<u>INTEGRATED MODULES</u>	<u>INSTALLATION INSTRUCTIONS</u>	<u>FIELD ENGR</u>
	32KB add-on MOS MEM	395-0070441	603-605105
	64KB add-on MOS MEM	395-0070442	603-605105
	128KB add-on MOS MEM*	395-0069037	603-605109
	256KB add-on MOS MEM*	395-0069037	603-605109
	Universal Dynamic Address* Translator (UDAT)	395-0069037	603-605105
	Asynchronous Adapter	395-0067103	603-600111
	Multi-Channel Communications Adapter (MCCA)	395-0070254	603-60017
	Integrated Disk Controller (IDC)	395-0067334	603-60004
	Bit Serial Link Adapter (BSLA)*	395-0069243	603-60511
	Buffered Trunk	395-0067241	603-60017
	Synchronous Message Level Adapter (SMLA)	395-0067104	603-60017
	Position Scanner	395-0070078	603-6001
	MCCA-to-MCCA Harness Kit	395-0070314	603-6001
	Second IDC Harness	395-0070296	603-6051

* These kits are only for the C6080 Extended Memory processor and the (